

PEARL INTEGRATED SUSPENSION SYSTEM

I.S.S.

取扱説明書 / Instruction Manual

この度は、I.S.S. タムマウントシステムをお買い上げいただき誠にありがとうございます。
製品の機能を十分に発揮してお使いいただくために、この取扱説明書をぜひご覧ください。

Congratulations on your purchase!

To get optimum performance of your I.S.S. Integrated Suspension System,
please read this Instruction Manual before playing.

I.S.S.本体フックのキーボルトを緩め、図のようにタムの上部フープにフックを引っ掛けてください。
ベースプレートをフープのエッジの下にはめ、I.S.S.が二つのチューニングロッドの中間に来るように位置を調整し、キーボルトを締めて固定します(図1)。
これで、I.S.S.の取り付けは完了です(図2)。

To attach the I.S.S. mount, loosen the Key Bolts on the Hooks and clip the hooks over the upper hoop of the tom as shown. Slip the Base Plate under the edge of the hoop and center the I.S.S. between the two nearest lugs then tighten the Key Bolts securely (Fig. 1, 2).
The I.S.S. mount can be quickly removed and reattached when changing heads.




図1




Fig.1

⚠ 注意

シエルを傷つけるのを避けるために、タムホルダーと、シエルが直接触れないように気を付けてください。

⚠ Caution

Keep a space between the end of the Tom Holder and the surface of the drum to prevent damage to the drum's finish.




図2




Fig.2